

Gaskets

Full face gaskets

Stock code **GFFCAF** and **GFFRI**

Available in a wide range of materials including

- Compressed asbestos plain
- Compressed asbestos graphited
- Compressed asbestos wire reinforced
- Non asbestos
- Teflon
- Neoprene bonded cork
- Cork
- Rubber Insertion
- Sweet red rubber
- Oilite
- Neoprene
- Acid



Sizes 2" to 12" (50mm to 300mm).



KINGFISHER'S COMMENTS: Other materials and sizes are obtainable within 24 hours.

Ring gaskets

Stock code **GRCAF** and **GRRRI**

Available in a wide range of materials including

- Compressed asbestos plain
- Compressed asbestos graphited
- Compressed asbestos wire reinforced
- Non asbestos
- Teflon
- Neoprene bonded cork
- Cork
- Rubber Insertion
- Sweet red rubber
- Oilite
- Neoprene
- Acid



Sizes 2" to 12" (50mm to 300mm).




KINGFISHER'S COMMENTS: Other materials and sizes are obtainable within 24 hours.

Gasketing material

Vellamoid

Stock code **GV**

Comes in 1 meter wide roll and thicknesses of 0.4mm, 0.8mm, 1-5mm and 3mm.



KINGFISHER'S COMMENTS: Ideally suited as a gasket for petrol and oil at 120°C

Gasketing material continued



Gasket sheeting

Available in a wide range of materials including

- Compressed asbestos plain
- Compressed asbestos graphited
- Compressed asbestos wire reinforced
- Non asbestos
- Teflon
- Neoprene bonded cork
- Cork
- Rubber Insertion
- Sweet red rubber
- Oilite
- Neoprene
- Acid

Other

PTFE thread seal tape



Stock code PTFE

Manufactured from Duraport teflon, non toxic, non reactive. Impervious to most acids, alkalis, chemicals, corrosives, fuels, Hydraulic fluids and oil solvents.

Suitable for temperatures between -100 C and +240 °C

An oxygen grade tape is available for use on oxygen, Freon, ammonia and other industrial gasses.

Stock code	PTFE012	PTFE020	PTFE025
Size	12mm x 0.075 x 10m	19mm x 0.075 x 10m	25mm x 0.075 x 10m